Claims

[c1] 1.A method for tracing the execution path of a computer program comprising at least one module including a plurality of instructions, at least one of said instructions being a branch instruction, the method comprising

identifying each branch instruction;

the steps of:

evaluating each branch instruction to be one of true and false; and responsive to an evaluation of true, pushing a unique identifier into a predefined area of storage, wherein said unique identifier is associated with the instructions executed as a result of said evaluation of true.

[c2]5^{W9}

2. The method of claim 1, wherein said predefined area of storage is in volatile memory.

[c3] 3.The method of claim 1, wherein said predefined area of storage is in non-volatile memory.

[c4] 4. The method of claim 1, comprising the step of:
outputting the contents of said storage area to a file at a predetermined
point in time.

[c5] 5. The method of claim 4, comprising the step of:
outputting trace information to said file upon exit from said at least one module.

[c6] 6. The method of claim 5, wherein the contents of said storage area is outputted at the same time as said exit trace information.

[c7] 7.The method of claim 4, wherein the step of outputting the contents of said storage area comprises:

determining whether said storage area is full; and responsive to a positive determination, outputting said contents to said file.

[c8]
8. The method of claim 4, wherein the step of outputting the contents of said storage area comprises:

determining whether a failure has occurred within said program; and responsive to a positive determination, outputting said contents to said file.

[c9]

9. The method of claim 4, wherein the step of pushing a unique identifier into a predefined area of storage further comprises the steps of: determining whether said predefined area of storage is full; and overwriting the first unique identifier in said storage area.

[c10] 5/7/2

writing the position of the most recent unique identifier to be written out to said storage area to said storage area.

[c11]

11. The method of claim 10, wherein said position is used to determine the number of unique identifiers that have been overwritten prior to being written out to said file.

[c12]

12. The method of claim 11, comprising the step of: responsive to determining that a large number of unique identifiers have been overwritten, increasing the size of said predefined area of storage.

[c13]

13.An apparatus for tracing the execution path of a computer program comprising at least one module including a plurality of instructions, at least one of said instructions being a branch instruction, said apparatus comprising:

means for identifying each branch instruction;

means for evaluating each branch instruction to be one of true and false; and means, responsive to an evaluation of true, for pushing a unique identifier into a predefined area of storage, wherein said unique identifier is associated with the instructions executed as a result of said evaluation of true.

[c14]

14.A method for instrumenting a computer program comprising at least one module including a plurality of instructions, at least one of said instructions being a branch instruction, each branch instruction being evaluated to be one of true and false at run-time, with at least one signature instruction for indicating the execution path of said program at run-time, the method

comprising the steps of:

identifying each branch instruction;

identifying the instructions associated with an evaluation of true at run-time; instrumenting said instructions associated with an evaluation of true with a signature instruction, wherein said signature instruction causes a unique identifier to be pushed into a predefined area of storage upon execution of said true instructions at run-time.

[c15] كلكو [C7]

One module including a plurality of instructions, at least one of said instructions being a branch instruction, each branch instruction being evaluated to be one of true and false at run-time, with at least one signature instruction for indicating the execution path of said program at run-time, said compiler comprising:

means for identifying each branch instruction;

means for identifying the instructions associated with an evaluation of true at run-time;

means for instrumenting said instructions associated with an evaluation of true with a signature instruction, wherein said signature instruction causes a unique identifier to be pushed into a predefined area of storage upon execution of said true instructions at run-time.